Early Journal Content on JSTOR, Free to Anyone in the World

This article is one of nearly 500,000 scholarly works digitized and made freely available to everyone in the world by JSTOR.

Known as the Early Journal Content, this set of works include research articles, news, letters, and other writings published in more than 200 of the oldest leading academic journals. The works date from the mid-seventeenth to the early twentieth centuries.

We encourage people to read and share the Early Journal Content openly and to tell others that this resource exists. People may post this content online or redistribute in any way for non-commercial purposes.

Read more about Early Journal Content at http://about.jstor.org/participate-jstor/individuals/early-journal-content.

JSTOR is a digital library of academic journals, books, and primary source objects. JSTOR helps people discover, use, and build upon a wide range of content through a powerful research and teaching platform, and preserves this content for future generations. JSTOR is part of ITHAKA, a not-for-profit organization that also includes Ithaka S+R and Portico. For more information about JSTOR, please contact support@jstor.org.

and

$$\left(\frac{dk}{dx}\right)^2+\left(\frac{dk}{dy}\right)^2+\left(\frac{dk}{dz}\right)^2+4\frac{dk}{dh}=0.$$

In this case we find $\psi(h)=\big((a^2+h)(b^2+h)(c^2+h)\big)^{\frac{1}{2}}$, and the above general expressions lead to the known results.

II. Supplement to a Paper, read January 27, 1859, "On the Thermodynamic Theory of Steam-engines with dry Saturated Steam, and its application to practice." By W. J. Macquorn Rankine, C.E., F.R.S. &c.*

(Abstract.)

This supplement gives the dimensions, tonnage, indicated horse-power, speed, and consumption of fuel, of the steam-ships whose engines were the subjects of the experiments referred to in the original paper. Results are arrived at respecting the available heat of combustion of the coal employed, and the efficiency of the furnaces and boilers, of which the following is a summary:—

No. of experiment.	Kind of boiler.	Total heat of combustion of 1 lb. of coal in ft.-lbs., estimated from chemical composition.	Available heat of combustion of 1 lb. of coal in ft.-lbs. computed from efficiency of steam and weight of coal burned per I.H.P.	*Available heat*, total heat, = efficiency of furnace and boiler.
I.	Improved Marine Boilers of ordinary proportions.	10,000,000	5,420,000	0·542
III.		10,000,000	5,300,000	0·53
II.	Boiler chiefly composed of small vertical water-tubes, with very great heating surface.	11,560,000	10,110,000	0·88

$$\text{Available Heat of Combustion of 1 lb. of coal} = \frac{1{,}980{,}000 \text{ ft.-lbs.}}{\text{Efficiency of steam} \times \text{lb. coal per I. H. P. per hour}}.$$

* Phil. Trans. 1859, p. 177; and Proceedings of the Royal Society, vol. ix. p. 626.